

PRODUCT SPECIFICATIONS FOR 259D3



ENGINE

Gross Power - SAE J1995	74.3 HP
Displacement	203 in ³
Net Power	73.2 HP
Bore	3.7 in
Engine Model	Cat C3.3B DIT (turbo)
Gross Power	74.3 HP
Net Power - SAE 1349	73.2 HP
Stroke	4.7 in
Peak Torque - 1,500 rpm - SAE J1995	195 ft·lbf
Net Power - ISO 9249	73.9 HP

OPERATING SPECIFICATIONS

Rated Operating Capacities - 35% Tipping Load	2010 lb
Tipping Load	5745 lb
Breakout Force - Tilt Cylinder	4965 lb
Ground Contact Area - With 320 mm/12.6 in Track	1483 in ²

**Ground Pressure -
With 320 mm/12.6 in
Track** 6.1 psi

**Rated Operating
Capacities - 50%
Tipping Load** 2870 lb

**Ground Contact Area -
With 400 mm/15.7 in
Track** 1848 in²

**Rated Operating
Capacity with Optional
Counterweight** 3060 lb

**Ground Pressure -
With 400 mm/15.7 in
Track** 4.9 psi

Note Operating Weight, Operating Specifications and Dimensions all based on 75 kg (165 lb) operator, all fluids, two speed, OROPS, 1730 mm (68 in) low profile bucket, 320 mm (12.6 in) tracks, dual flange front idler/single flange rear idler, standard flow hydraulics, mechanical suspension seat, no optional counterweights and manual quick coupler (unless otherwise noted).

WEIGHTS

**Operating
Weight** 8987 lb

Note Operating Weight, Operating Specifications and Dimensions all based on 75 kg (165 lb) operator, all fluids, two speed, OROPS, 1730 mm (68 in) low profile bucket, 320 mm (12.6 in) tracks, dual flange front idler/single flange rear idler, standard flow hydraulics, mechanical suspension seat, no optional counterweights and manual quick coupler (unless otherwise noted).

DIMENSIONS

**Length - Track on
Ground** 59 in

Overall Length - Track	78.7 in
Height - Top of Cab	83.1 in
Ground Clearance	8.9 in
Departure Angle	35°
Maximum Dump Angle	52°
Bucket Pin Height - Carry Position	7.8 in
Vehicle Width (400 mm/15.7 in tracks)	69 in
Turning Radius from Center - Coupler	54.8 in
Bucket Pin Reach - Maximum Lift	9.4 in
Vehicle Width (320 mm/12.6 in tracks)	66 in
Maximum Reach - With Arms Parallel to Ground	51.4 in
Maximum Overall Height	154.1 in
Turning Radius from Center - Bucket	86 in
Bucket Pin Height - Maximum Lift	121 in

Length - Without Bucket 108.9 in

Rack Back Angle - Maximum Height 87°

Note Operating Weight, Operating Specifications and Dimensions all based on 75 kg (165 lb) operator, all fluids, two speed, OROPS, 1730 mm (68 in) low profile bucket, 320 mm (12.6 in) tracks, dual flange front idler/single flange rear idler, standard flow hydraulics, mechanical suspension seat, no optional counterweights and manual quick coupler (unless otherwise noted).

Turning Radius from Center - Machine Rear 61.5 in

Length - With Bucket on Ground 137.3 in

Clearance at Maximum Lift and Dump 89.9 in

Reach - Maximum Lift/Dump 23.9 in

HYDRAULIC SYSTEM

Hydraulic Flow - High Flow - Loader Hydraulic Pressure 3335 psi

Hydraulic Flow - High Flow - Hydraulic Power (Calculated) 58 HP

Hydraulic Flow - Standard - Loader Hydraulic Pressure 3335 psi

Hydraulic Flow - Standard - Loader Hydraulic Flow 20 gal/min

Hydraulic Flow - Standard - Hydraulic Power (Calculated) 39 HP

Hydraulic Flow - High Flow - Loader Hydraulic Flow 30 gal/min

CAB

ROPS

ISO 3471:2008

FOPS

ISO 3449:2005 Level I

POWER TRAIN

Travel Speed - Forward or Reverse - One Speed

5.9 mile/h

Travel Speed - Forward or Reverse - Two Speed

8.5 mile/h

SERVICE REFILL CAPACITIES

Hydraulic System

13.2 gal (US)

Fuel Tank

24.8 gal (US)

Engine Crankcase

3 gal (US)

Hydraulic Tank

10.3 gal (US)

Cooling System

3.7 gal (US)

AIR CONDITIONING SYSTEM (IF EQUIPPED)

Air Conditioning

The air conditioning system on this machine contains the fluorinated greenhouse gas refrigerant R134a (Global Warming Potential = 1430). The system contains 0.81 kg of refrigerant which has a CO2 equivalent of 1.158 metric tonnes.

NOISE LEVEL

Note (3)

***The labeled sound power level for the CE marked configurations when measured according to the test procedure and conditions specified in 2000/14/EC.

Outside Cab***

103 dB(A)

Inside Cab**

83 dB(A)

Note (2)

**The declared dynamic operator sound pressure levels per ISO 6396:2008. The measurements were conducted with the cab doors and windows closed and at 70% of the maximum engine cooling fan speed. The sound level may vary at different engine cooling fan speeds.

Note (1)

Cab and Rollover Protective Structures (ROPS) are standard in North America and Europe.

259D3 STANDARD EQUIPMENT

ELECTRICAL

12 volt Electrical System

80 ampere Alternator

Ignition Key Start/Stop Switch

Lights: Gauge Backlighting, Two Rear Tail Lights, Two Adjustable Front and Rear Halogen Lights, Dome Light
Backup Alarm

Heavy Duty Battery, 850 CCA

OPERATOR ENVIRONMENT

Advanced Display with Rearview Camera: Full Color, 127 mm (5 in) LCD screen; Advanced Multi-operator Security System; On-screen Adjustments for Implement Response, Hystat Response, and Creep Control
Gauges: Fuel Level, Hour Meter

Operator Warning System Indicators: Air Filter Restriction, Alternator Output, Armrest Raised/Operator Out of Seat, Engine Coolant Temperature, Engine Oil Pressure, Glow Plug Activation, Hydraulic Filter Restriction, Hydraulic Oil Temperature, Park Brake Engaged, Engine Emission System

Adjustable Vinyl Seat

Fold In Ergonomic Contoured Armrest

Control Interlock System, when operator leaves seat or armrest raised: Hydraulic System Disables, Hydrostatic Transmission Disables, Parking Brake Engages

ROPS Cab, Open, Tilt Up

FOPS, Level I

Top and Rear Windows

Floor Mat

Interior Rearview Mirror

12 volt Electric Socket

Horn

Hand (Dial) Throttle, Electronic

Adjustable Joystick Controls

Anti-theft Security System with 6-button Keypad

Storage Compartment with Netting

POWER TRAIN

Cat C3.3B, Turbo Diesel Engine, Meeting Tier 4 Final and Stage V Emission Standards

Air Cleaner, Dual Element, Radial Seal

S·O·SSM Sampling Valve, Hydraulic Oil

Filters, Cartridge-type, Hydraulic

Filters, Canister-type, Fuel and Water Separator

Radiator/Hydraulic Oil Cooler (side-by-side)

Spring Applied, Hydraulically Released Parking Brakes

Hydrostatic Transmission, Two Speed Travel

Suspension – Independent Torsion Axles (4)

OTHER

Engine Enclosure, Lockable

Extended Life Antifreeze, -36° C (-33° F)

Machine Tie Down Points (6)

Support, Lift Arm

Hydraulic Oil Level Sight Gauge

Radiator Coolant Level Sight Gauge

Radiator, Expansion Bottle

Cat ToughGuard™ Hose

Auxiliary, Hydraulics, Continuous Flow

Heavy Duty, Flat Faced Quick Disconnects with Integrated Pressure Release

Split D-Ring to Route Work Tool Hoses Along Side of Left Lift Arm

Electrical Outlet, Beacon

Belly Pan Cleanout

Variable Speed Demand Fan

Product Link™ PL240, Cellular

MANDATORY EQUIPMENT

Hydraulics, Standard or High Flow

Quick Coupler, Mechanical or Powered

High Visibility Seat Belt, 50 mm (2 in) or 75 mm (3 in)

EU Preparation Package

Steel Imbed Rubber Track – 320 mm (12.6 in) or 400 mm (15.7 in)

Dual Flange Front Idler/Single Flange Rear Idler or Triple Flange Front/Rear Idlers

PERFORMANCE PACKAGES:

– Performance Package H1: Standard Flow Hydraulics (No Self Level)

– Performance Package H2: Standard Flow Hydraulics, Dual Direction Electronic Self Level (Raise and Lower), Work Tool Return to Dig, Work Tool Positioner, and Electronic Snubbing (Raise and Lower)

– Performance Package H3: High Flow Hydraulics, Dual Direction Electronic Self Level (Raise and Lower), Work Tool Return to Dig, Work Tool Positioner, and Electronic Snubbing (Raise and Lower)

PACOTES DE CONFORTO:

– ROPS aberto (C0): Assento estático (sem pedal do acelerador, forro do teto, aquecedor ou porta)

– ROPS aberto (C1): Acelerador do pé, forro do teto, porta-copos e opção de assento (suspensão mecânica ou encosto alto, aquecido, Assento Air Ride) (Sem Aquecedor ou Porta)

– ROPS Fechado com Aquecedor (C2): Acelerador de pé, forro do teto, aquecedor e desembaçador, janelas laterais, porta-copos, rádio pronto, opção de assento (suspensão mecânica ou encosto alto, aquecido, Assento Air Ride) e Porta (Vidro ou Policarbonato)

– ROPS Fechado com A/C (C3): C2 + Ar Condicionado

259D3 EQUIPAMENTO OPCIONAL

EQUIPAMENTO OPCIONAL

Controles estilo mão-pé

Contrapesos Externos

Farol, Rotativo

Aquecedor do Bloco do Motor - 120V

Óleo, Hidráulico, Operação a Frio

Pintura, Personalizada

Link do produto PL641, celular

Controle de condução sensível à velocidade

Rádio Bluetooth® com microfone (AM/FM/receptor de banda meteorológica com USB e tomada de entrada auxiliar)